

3. Technical specifications and hall and open-air site equipment  
3.1 Hall specifications

Specifications & facts		ÖVB Arena (Hall 1)	Main foyer ÖVB Arena	Hall 2	Hall 3	Hall 4.0	Foyer Hall 4.0	Hall 4.1	Foyer Hall 4.1 incl. passageway to the Congress Centre (CCB) <sup>10)</sup>	Hall 5	Foyer Hall 5	Hall 6	Foyer Hall 6	Hall 7
Hall specifications	Location	Level 0	Level 0	Level 0	Level 0	Level 0	Level 0	Level 1	Level 1	Level 0	Level 0	Level 0	Level 0	Level 0
	Length (in m)	77.50		66.00	70.00	54.50	54.50	54.50	54.50	117.50	117.50	54.50	54.50	75.00
	Width (in m)	40.00		29.50	23.50	79.50	20.50	39.50	6.50	88.00	12.00	88.00	12.00	54.00
	Clear height (in m) <sup>1)</sup>	19.80 - 25.50	14.00	4.70	2.45 - 5.90	3.70 - 11.50	4.50	4.70	2.90 - 6.30	11.50	4.50	11.50	4.50	12.00
Exhibition area (gross in sq m)		2,750	1,100	2,000 <sup>2)</sup>	1,750 <sup>2)</sup>	4,300 <sup>2)</sup>	980 <sup>8)</sup>	2,100	As agreed	10,300	1,100 <sup>2)</sup>	4,800	550 <sup>2)</sup>	4,000
Access/delivery		Gate C/D	Gate C/D	Gate D	Gate D	Gate E/F	Gate E/F	Gate D/E	Gate D/E	Gate E/F	Gate E/F	Gate E/F	Gate E/F	Gate G
Hall gates	Height (in m)	4.20	2.70	4.20	2.45 / 2.85	5.20 <sup>4)</sup>	4.20	See Lifts	See Lifts	5.20 <sup>4)</sup>	4.20	5.20 <sup>4)</sup>	4.20	4.30 / 4.00
	Width (in m)	3.80	3.40	4.10	5.50 / 5.50	5.40 <sup>4)</sup>	5.10	See Lifts	See Lifts	5.40 <sup>4)</sup>	5.10	5.40 <sup>4)</sup>	4.60	4.50 / 4.10
Lifts		Freight lift from Hall 2/4 to Hall 4.1: door dimensions: 2.41 m wide, 2.45 m high, interior dimensions: 3.34 m wide, 4.31 m long; 2.64 m height; load capacity 3.0 t												
Floor and ground surfaces		Asphalt	Artificial stone	Asphalt	Artificial stone	Asphalt	Artificial stone	Artificial stone	Artificial stone	Asphalt	Artificial stone	Asphalt	Artificial stone	Asphalt
Floor load/area load		150 kN/m <sup>2</sup>		150 kN/m <sup>2</sup>		150 kN/m <sup>2</sup>	5 kN/m <sup>2</sup> <sup>3)</sup>	5 kN/m <sup>2</sup>	5 kN/m <sup>2</sup>	150 kN/m <sup>2</sup>	5 kN/m <sup>2</sup> <sup>3)</sup>	150 kN/m <sup>2</sup>	5 kN/m <sup>2</sup> <sup>3)</sup>	150 kN/m <sup>2</sup>
Glass facade		No	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Options for suspending objects		Upon request	Upon request			Upon request		Upon request		Upon request		Upon request		Upon request
Lighting (d) = dimmable	Type	LED/Fluorescent mix (d)	Various (d)	LED (d)	LED (d)	LED (d)	LED (d)	LED (d)	LED (d)	LED (d)	LED (d)	LED (d)	LED (d)	LED (d)
	Max. brightness (lux)	2,000	500	300	300	360	200	300	200	360	200	360	200	1,600
Sprinkler system		No	No	No	No	Yes	Yes	Yes	Yes	No	Yes	No	Yes	No
Smoke detectors		Yes	Yes	Yes	Yes	Yes <sup>6)</sup>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Media connections <sup>5)</sup>		P, E, M	P, E	P, E	P, E	M	P, E	P, E	P, E	M	P, E	M	P, E	E, M
LAN		min. 2Mbit/s per port												
W-LAN		In all halls (performance may vary depending on user numbers)												
Seating capacity <sup>9)</sup>	Standing <sup>9)</sup>	14,000		2,500		5,500		2,200		11,000		5,500		7,000
	Rows	10,445 incl. standing	Upon request	660 in 3 mobile spaces -		2,000		1,750 or 3x300 5x200		5,000		2,000		4,000
	Classroom-style	1,100	Upon request			1,000		850		2,500		1,000		1,500
	Bench	2,000	Upon request	-	-	1,850		1,000		4,000		1,850		2,000

<sup>1)</sup> Restrictions due to ventilation are not taken into account

<sup>2)</sup> Limited area due to pillars

<sup>3)</sup> No industrial trucks except for the access roads  
Max. permitted traffic load of 30 kN/m<sup>2</sup> as per DIN 1055

<sup>4)</sup> North Hollerallee entrance

<sup>5)</sup> P = Portable outlet, E = Electricity outlet,  
M = Media outlets

<sup>6)</sup> In lower part of Hall 4

<sup>7)</sup> Only in front part of Hall 4

<sup>8)</sup> Area limited by escalator

<sup>9)</sup> Generally depends on event set-up

<sup>10)</sup> CCB = Bremen Congress Centre